Doormerica

Mullion 7100 - For use with Non-Rated Rim Exit Devices on non-rated pairs of doors


Specifications:

Mullion Size	2" x 3" x 96" Steel Tube. Mullion may be field cut to fit proper size.
Rim Cylinder	. Use 1-1/4" Rim Cylinder, cylinder not included. 1/2" spacer required. Not included.
Top Bracket	. Steel, using key allows the mullion to be removed in seconds.
	Mullion can be locked in top bracket easily without using the key.
Bottom Bracket	. Steel, fixed by 4 hex bolts with Stainless Steel anchors.
Strike	. Use two standard Rim Strikes, not included
Finish	. Gray baked powder coating only


Mullion 7100F - For use with Fire-Rated Rim Exit Devices on fire-rated pairs of doors

Specifications:

Mullion Size	2" x 3" x 96" Steel Tube. Mullion may be field cut to fit proper size.
Rim Cylinder	Use 1-1/4" Rim Cylinder, cylinder not included. 1/2" spacer required. Not included.
Top Bracket	Stainless Steel, using key allows the mullion to be removed in seconds.
	Mullion can be locked in top bracket easily without using the key.
Bottom Bracket Stainless Steel, fixed by 4 hex bolts with Stainless Steel anchors.	
Strike Use two (2)	sets of Mullion Strikes (688) & Strike Hooks (689) - Not Included. (Part No. MULL7100FSTRIKEPACK)
Finish	Gray baked powder coating only



The removable Mullion is used for with two Rim Devices on double doors.



FOR USE WITH FIRE-RATED

Top Bracket

Bottom Bracket

Mullion Strike

Strike Hook

FOR USE WITH NON-RATED



Top Bracket

B

Bottom Bracket

Rim Strike

Stocked Product

Item MULL7100 MULL7100F MULL7100FSTRIKEPACK **Description** Mullion Non-Rated Mullion Fire-Rated Fire Rated Mullion Pack