

Doormerica

EDR701 / EDFR701 -

Heavy Duty Grade 1 Rim Exit Device



Features:

- Chassis mounted unit construction.
- Minimum style 4-1/2".
- Standard door thickness 1-3/4".
- For all doors up to 36".
- Universal design retrofits on Von Duprin 99 series & Sargent 88 Series.
- Material: Cover, and cap and rail are made of brass, bronze or Stainless Steel.
- 161 ANSI cutout.
- Mounting: Furnished with wood & machine screws. Thru bolts, standard on fire rated devices.
- Non Handed.
- Latch Bolt: Stainless Steel 3/4"

Dimensions:

Touchbar	Height to finish floor 41" at center
Touchbar	Projection
	Neutral 2-1/2"
	Depressed 1-3/4"
Center case 8-1/2" x 2-1/2" x 2"
Device Length	Standard 2'2" - 3'
	Long (L) 2'9" - 4'

Options:

- Stocked 48" length, specify "L"
- Available different functions. Lever escutcheon trims are Grade 1 construction with clutch free wheeling mechanism. Covers 161 cutout, see page 11.
- ALRMKIT700 Alarm Kit available for 3' & 4' applications.
- Glass Bead Kits available.

Specifications:

- All exit devices shall be of touch bar design with smooth operation and be operative over 2/3 of the door's clear opening width.
- All exit devices must be listed under "Panic Hardware" in the Accident Equipment List of Underwriter's Laboratories, Inc. Where labeled doors are used as exits, they must be equipped with labeled Fire Exit Hardware and UL 10C, UBC 7-2-1997 codes.
- All exit devices shall be of chassis mounted unit construction.



CODE COMPLIANCE:

- ANSI A165.3, Grade 1
- UL listed for Panic and UL 10C, UBC 7-2-1997 codes.
- UL listed for Fire Exit Hardware. 3 Hours.
- (A) label rating on pairs of doors up to 8'0" x 8'0" swinging in same or opposite directions.

LIMITED LIFETIME WARRANTY

Stocked Product

Item	Finish
EDR701	10B, 28, 32D 36" & 48" length applications
EDFR701	10B, 28, 32D 36" & 48" length applications